

IEC telecom



CERTUS[®] C 700



MARITIME

Truly global connectivity for all vessels





**POLE-TO-POLE
COVERAGE**

**12-ELEMENT PATCH
TECHNOLOGY**

**FASTEST L-BAND
BROADBAND SERVICE**

HD QUALITY VOICE LINES

**NO MAINTENANCE
REQUIRED OVER
OPERATIONAL LIFETIME**

Offering truly global pole-to-pole coverage, Certus® C 700 is powered by the Iridium Certus® network of 66 LEO satellites and can be deployed as the primary onboard communications antenna or as a companion to the existing VSAT system. With the fastest L-Band broadband service in the industry, the terminal simultaneously supports three HD quality, low-latency voice lines and can deliver uplink speeds of 352 Kbps and downlink speeds of 704 Kbps to ensure seamless connectivity in all weather conditions.

From built-in ATA and onboard PABX to PoE, the terminal provides excellent performance during any ship motion and low satellite elevation angles. Its 12-element patch technology, VSAT + C 700 Bundled Packages, and support for multiple onboard users make it the perfect VSAT companion for the maritime sector. The all-in-one Certus® C 700 terminal is a solid-state antenna with no moving parts, requiring no scheduled maintenance over its lifetime.

CHARACTERISTICS

- Weight
 - ADU: 7.3 kg
 - BDU: 1.2 kg
- Dimensions
 - ADU: 370 x 270 mm
 - BDU: 280 x 183.5 x 41 mm
- Operational Temperature
 - ADU (°C): -25°C to +55°C
 - BDU (°C): -15°C to +55°C
- Operating Humidity: > 95%
- Power Supply Voltage: 10.8 V to 30 V DC
- Output Power: 120 W
- IP Data: Up to 352 Kbps (uplink); Up to 704 Kbps (downlink)
- Ingress Protection
 - ADU: IP56
 - BDU: IP31
- Antenna TNC
- 3 Simultaneous HD Quality Voice Lines
- 3 x RJ45 LAN
- 3G/4G/LTE WAN Port
- 2 Analog Phones
- 10 pin GPIO
- SIM
- GMDSS Ready
- Built-in WiFi
- Built-in Firewall
- Soft PABX & LTE Interface Capability

IN THE BOX

- Intellian C 700 Terminal
- Below Deck Unit
- Power Supply Kit